BookletChart™

Unakwik Inlet to Esther Passage and College Fiord

NOAA Chart 16712

A reduced-scale NOAA nautical chart for small boaters

When possible, use the full-size NOAA chart for navigation.

- Complete, reduced-scale nautical chart
- Print at home for free
- Convenient size
- Up-to-date with Notices to Mariners
- Compiled by NOAA's Office of Coast Survey, the nation's chartmaker



Published by the
National Oceanic and Atmospheric Administration
National Ocean Service
Office of Coast Survey
www.NauticalCharts.NOAA.gov
888-990-NOAA

What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

What is a BookletChart™?

This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.

Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at http://www.NauticalCharts.NOAA.gov.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

Notice to Mariners Correction Status

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.

For latest Coast Pilot excerpt visit the Office of Coast Survey website at http://www.nauticalcharts.noaa.gov/nsd/searchbychart.php?chart=16712.



(Selected Excerpts from Coast Pilot)
South Bay is on the E side of Perry Island Light. Good anchorage is available for moderate-size vessels in 10 to 24 fathoms, sand and mud bottom, in the cove at the head of the bay. When entering, avoid the rocks that extend almost 0.2 mile from the E side of the entrance to the cove. An oyster farm is near the head of the cove.
East Twin Bay has anchorage for small craft near the center of the bay, about 0.8 mile from the head in 13 fathoms with a soft bottom. A midchannel course should be followed until a prominent rock about 20 feet high, near the center of the bay, bears S approximately 0.2 mile. The portion of the bay beyond the rock is navigable in spots, but should be avoided because the area is foul.
West Twin Bay is entered mid-channel, avoiding the chain of islands and foul ground extending for over a mile from the point of land on the W side on the entrance. Small craft entering should favor the NE side until past the narrow area about 1 mile from the head of the bay, and then favor the SW side, passing W of a rock about 15 feet high, near the middle of the bay 0.8 mile from the head. A 1½-fathom shoal exists just N of the narrow section approximately 0.1 mile from the point of land protruding NE from the W shore.
Anchorage is available in the bay for mid-sized vessels in 5 to 15 fathoms of water, mud bottom, in a bight about 0.7 mile S of the W point and about 0.1 mile N of the gravel spit extending from the E shore, and E of the rock in the middle of the bay. The area S of the gravel spit is shallow and rocky.
Perry Passage is between Perry Island and Culross Island, 2.5 miles to the W. Wells Passage, between Perry and Culross Islands on the S and Esther Island on the N, is over 2 miles wide. The two passages have depths of 100 to 250 fathoms. Caution should be exercised when approaching or departing the E end of Wells Passage. Numerous islands, islets, rocks, and shoals extend E and SE for about 5 to 9 miles.
Esther Island is mountainous, wooded to a height of about 1,000 feet, and the summits are bare rocks. The peak on the SE point of Esther Island, and the sharp twin peaks on the SW point, are prominent. **Point Esther Light** (60°47'08"N., 148°06'01"W.), 31 feet (9.5 m) above the water, is shown from a skeleton tower with a red and white diamond-shaped daymark on the SW side of the island. Three bays are between the light and Esther Passage. **Esther Bay**, the easternmost is 3.5 miles E of the light on Point Esther and extends N about 2 miles. The entrance, 0.7 mile wide, is partly blocked by several wooded islets, bare rocks, and rocks awash. The interior of the bay is dotted with islets and rocks.
Quillian Bay, the middle bay, 1.3 miles E of the light, extends 1.7 miles NNE, and is about 0.2 mile wide. The entrance is constricted to a width of 0.1 mile. An islet is 0.7 mile above the entrance and two rocks awash are toward the head of the bay. The shores are steep-to.
When transiting the bay from S, vessels are advised to stay midchannel between the easternmost islet and the E shore. Continuing N from the islets, the bay widens to 0.4 mile, average depth 12 fathoms. A foul area extends approximately 0.1 mile off the E shore at the widest part of the bay. About 0.45 mile N of the islets, the bay narrows to 0.1 mile with numerous rocks extending W from the E shore. Vessels should stay within 50 yards of the W shore until the bay starts widening again. Continuing N to the head of the bay, vessels should favor for the W shore. Average depth in the area is 3½ to 5¼ fathoms. The entrance to the lagoon NW of the head of the bay is blocked by a rock.
Lake Bay is 0.7 mile E of the light, extends 1.2 miles NW, and is about 0.2 mile wide. Fishing craft find indifferent anchorage near the E shore SE of the narrowest part where the bay widens to its maximum of 0.3 mile. Rocks awash extend about 110 yards SE of the point forming the NW extremity of the anchorage bight. A submerged rock is 0.3 mile from the head of the bay. In general, the shores are steep-to and depths are too great for convenient anchorage. About 0.5 mile from the head on the E side is a freshwater stream that discharges from Esther Lake. A fish hatchery and fish pens are near the stream.

U.S. Coast Guard Rescue Coordination Center
24 hour Regional Contact for Emergencies

RCC Juneau	Commander 17th CG District Juneau, Alaska	(907) 463-2000

Table of Selected Chart Notes

NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

Rugged I, AK	WNG-526	162.425 MHz
Naked I, AK	WNG-530	162.500 MHz
Point Pigot, AK	KZZ-93	162.450 MHz
Cape Hinchinbrook	WNG-532	162.525 MHz
Potato Point, AK	WNG-527	162.425 MHz
Wasilla, AK	KZZ-98	162.400 MHz
Valdez, AK	WXJ-63	162.55 MHz
Cordova, AK	WXJ-79	162.40 MHz
Whittier, AK	KXI-29	162.40 MHz

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Notice to Mariners.

During some winter months or when endangered by ice, certain aids to navigation are replaced by other types or removed. For details see U.S. Coast Guard Light List.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

CAUTION

SUBMARINE PIPELINES AND CABLES

Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

Pipeline Area *Cable Area*

Mercator Projection
Scale 1:50,000 at Lat. 60° 50'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FATHOMS
(FATHOMS AND FEET TO ELEVEN FATHOMS)
AT MEAN LOWER LOW WATER

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 1.883" southward and 7.446" westward to agree with this chart.

NOTE A

Navigation regulations are published in Chapter 2, U.S Coast Pilot 9. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 17th Coast Guard District in Juneau, Alaska, or at the Office of the District Engineer, Corps of Engineers In Anchorage, Alaska.

Refer to charted regulation section numbers.

HEIGHTS

Heights of rocks, bridges, landmarks and lights are in feet and refer to Mean High Water. Contour and Summit elevation values are in feet and refer to Mean Sea Level.

SOURCE DIAGRAM

The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the U. S. Coast Guard, Geological Survey, and National Imagery and Mapping Agency.

COLREGS, 80.1705 (see note A)

International Regulations for Preventing Collisions at Sea, 1972.
The entire area of this chart falls seaward of the COLREGS Demarcation Line.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

ABBREVIATIONS

(For complete list of Symbols and Abbreviations, see Chart No. 1.)

Aids to Navigation (lights are white unless otherwise indicated):

AERO aeronautical
Al alternating
B black
Bn beacon
C can
DIA diaphone
F fixed
Fl flashing
G green
IQ interrupted quick
Iso isophase
LT HO lighthouse
M nautical mile
m minutes
MICRO TR microwave tower
Mkr marker
Mo morse code
N nun
OBSC obscured
Oc occulting
Or orange
Q quick
R red
Ra Ref radar reflector
R Bn radiobeacon
R TR radio tower
Rot rotating
s seconds
SEC sector
St M statute miles
VQ very quick
W white
WHIS whistle
Y yellow

Bottom characteristics:

Blds boulders
bk broken
Cy clay
Co coral
G gravel
Grs grass
gy gray
h hard
M mud
Oys oysters
Rk rock
S sand
so soft
Sh shells
sy sticky

Miscellaneous:

AUTH authorized
ED existence doubtful
Obstn obstruction
PA position approximate
PD position doubtful
Rep reported
Subm submerged

(21) Wreck, rock, obstruction, or shoal swept clear to the depth indicated.
(2) Rocks that cover and uncover, with heights in feet above datum of soundings.

TIDAL INFORMATION

Place Name (LAT/LONG)	Height referred to datum of soundings (MLLW) Mean Higher High Water	Mean High Water	Mean Low Water	Extreme Low Water
	feet	feet	feet	feet
Gibbon Anchorage, Green Island (60°16'N/147°26'W)	11.5	13.5	1.3	-4.0
Snug Harbor, Cook Inlet (60°6'N/152°34'W)	15.7	14.9	1.7	-4.0
Port Audrey, Knight Island, Drier Bay (60°20'N/147°46'W)	12.1	11.2	1.6	-4.0
Eshamy Bay, Knight Island Passage (60°26'N/147°58'W)	12.1	11.2	1.5	-4.0

(699)

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.

16712

SOURCE DIAGRAM

The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot.

SOURCE			
A	1990-1999	NOS Surveys	full bottom coverage
B1	1990-1999	NOS Surveys	partial bottom coverage
B4	1900-1939	NOS Surveys	partial bottom coverage

Barry Glacier
Barnard Glacier
Wellesley Glacier
Coxe Glacier
Mt Coville 4570
Mt Emerson 5077
FIORD
COLLEGE
Coghill River
Reef
Joins page 8

Printed at reduced scale.

SCALE 1:50,000

Nautical Miles: 1 0 1 2 3 4

Yards: 1000 0 1000 2000 3000 4000 5000 6000

See Note on page 5.

Note: Chart grid lines are aligned with true north.

1st Ed., May 1999 KAPP 2960

JOINS CHART 16711

51' 50' 49' 48' 47' 46' 45' 44' 43' 42' 41' 40' 39' 38' 37'



UNITED STATES

ALASKA - SOUTH COAST

UNAKWIK INLET TO ESTHER P
AND COLLEGE FIORD

PRINCE WILLIAM SOUND

Coghill Lake

Mercator Projection
Scale 1:50,000 at Lat. 60° 50'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FATHOMS
(FATHOMS AND FEET TO ELEVEN FATHOMS)
AT MEAN LOWER LOW WATER

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)
Aids to Navigation (lights are white unless otherwise indicated):

AERO aeronautical	G green	Mo morse code	R TR radio tower
Al alternating	IQ interrupted quick	N nun	Rot rotating
B black	Iso isophase	OBSC obscured	s seconds
Bn beacon	LT HO lighthouse	Oc occulting	SEC sector
C can	M nautical mile	Or orange	St M statute miles
DIA diaphone	m minutes	Q quick	VQ very quick
F fixed	MICRO TR microwave tower	R red	W white
Fl flashing	Mkr marker	Ra Ref radar reflector	WHIS whistle
		R Bn radiobeacon	Y yellow

Bottom characteristics:

Blds boulders	Co coral	gy grey	Oys oysters	so soft
bk broken	G gravel	h hard	Rk rock	Sh shells
Cy clay	Grs grass	M mud	S sand	sy sticky

Miscellaneous:

AUTH authorized	Obstn obstruction	PD position doubtful	Subm submerged
ED existence doubtful	PA position approximate	Rep reported	

(21) Wreck, rock, obstruction, or shoal swept clear to the depth indicated.
(2) Rocks that cover and uncover, with heights in feet above datum of soundings.

HEIGHTS

Heights of rocks, bridges, landmarks and lights are in feet and refer to Mean High Water. Contour and Summit elevation values are in feet and refer to Mean Sea Level.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the U. S. Coast Guard, Geological Survey, and National Imagery and Mapping Agency.

NOTE A

Navigation regulations are published in Chapter 2, U.S Coast Pilot 9. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 17th Coast Guard District in Juneau, Alaska, or at the Office of the District Engineer, Corps of Engineers In Anchorage, Alaska.

Refer to charted regulation section numbers.

SUPPLEMENTAL INFORMATION

Joins page 6

Joins page 9

This BookletChart was reduced to 75% of the original chart scale.
The new scale is 1:66667. Barscales have also been reduced and
are accurate when used to measure distances in this BookletChart.

1st Ed., May 1999 KAPP 2960

JOINS CHART 16711



Joins page 5

Joins page 10

NOAA
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
U.S. DEPARTMENT OF COMMERCE
COAST SURVEY

UNITED STATES

ALASKA - SOUTH COAST

UNAKWIK INLET TO ESTHER PAS AND COLLEGE FIORD

PRINCE WILLIAM SOUND

Mercator Projection
Scale 1:50,000 at Lat. 60° 50'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FATHOMS
(FATHOMS AND FEET TO ELEVEN FATHOMS)
AT MEAN LOWER LOW WATER

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)
Aids to Navigation (lights are white unless otherwise indicated):

AERO aeronautical	G green	Mo morse code	R TR radio tower
Al alternating	IQ interrupted quick	N nun	Rot rotating
B black	Iso isophase	OBSC obscured	s seconds
Bn beacon	LT HO lighthouse	Oc occulting	SEC sector
C can	M nautical mile	Or orange	St M statute miles
DIA diaphone	m minutes	Q quick	VQ very quick
F fixed	MICRO TR microwave tower	R red	W white
Fl flashing	Mkr marker	Ra Ref radar reflector	WHIS whistle
		R Bn radiobeacon	Y yellow

Bottom characteristics:

Blds boulders	Co coral	gy gray	Oys oysters	so soft
bk broken	G gravel	h hard	Rk rock	Sh shells
Cy clay	Grs grass	M mud	S sand	sy sticky

Miscellaneous:

AUTH authorized	Obstn obstruction	PD position doubtful	Subm submerged
ED existence doubtful	PA position approximate	Rep reported	

(21) Wreck, rock, obstruction, or shoal swept clear to the depth indicated.
(2) Rocks that cover and uncover, with heights in feet above datum of soundings.

HEIGHTS

Heights of rocks, bridges, landmarks and lights are in feet and refer to Mean High Water. Contour and Summit elevation values are in feet and refer to Mean Sea Level.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the U. S. Coast Guard, Geological Survey, and National Imagery and Mapping Agency.

NOTE A

Navigation regulations are published in Chapter 2, U.S Coast Pilot 9. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 17th Coast Guard District in Juneau, Alaska, or at the Office of the District Engineer, Corps of Engineers In Anchorage, Alaska.

Refer to charted regulation section numbers.

SUPPLEMENTAL INFORMATION

Note: Chart grid lines are aligned with true north.

Printed at reduced scale. ~~SCALE 1:50,000~~ See Note on page 5.

Nautical Miles
1 0 1 2 3 4

Yards
1000 0 1000 2000 3000 4000 5000 6000

SOUNDINGS IN FATHOMS

(FATHOMS AND FEET TO 11 FATHOMS)

Nautical Chart Catalog No. 3, Panel L

16712



This BookletChart has been updated through: Coast Guard Local Notice To Mariners: 4812 11/27/2012, NGA Weekly Notice to Mariners: 4812 12/1/2012, Canadian Coast Guard Notice to Mariners: 0912 9/28/2012.



8

Note: Chart grid lines are aligned with true north.

Printed at reduced scale.

SCALE 1:50,000

Nautical Miles

1 0 1 2 3 4

Yards

1000 0 1000 2000 3000 4000 5000 6000

See Note on page 5.


Joins page 5
NOTE A
Navigation regulations are published in Chapter 2, U.S Coast Pilot 9. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 17th Coast Guard District in Juneau, Alaska, or at the Office of the District Engineer, Corps of Engineers In Anchorage, Alaska.
Refer to charted regulation section numbers.
SUPPLEMENTAL INFORMATION
Consult U.S. Coast Pilot 9 for important supplemental information.
MAGNETIC
VAR 23°30'E (1999)
ANNUAL DECREASE 12'
Williams Glacier
3914
4078
Lafayette Glacier
2999
herst Glacier
Glacier
4652
2520
2152
2979
Jonah Ba
Siwash Bay
Joins page 10
Joins page 13



10

Note: Chart grid lines are aligned with true north.

Printed at reduced scale.

~~SCALE 1:50,000~~

Nautical Miles

1 0 1 2 3 4

Yards

1000 0 1000 2000 3000 4000 5000 6000

See Note on page 5.


Joins page 7
Miners Lake
Miners Bay
CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart. See Notice to Mariners.
During some winter months or when endangered by ice, certain aids to navigation are replaced by other types or removed. For details see U.S. Coast Guard Light List.
NOAA WEATHER RADIO BROADCASTS
The NOAA Weather Racio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.
Rugged I, AK WNG-526 162.425 MHz
Naked I, AK WNG-530 162.500 MHz
Point Pigot, AK KZZ-93 162.450 MHz
Cape Hinchinbrook WNG-532 162.525 MHz
Potato Point, AK WNG-527 162.425 MHz
Wasilla, AK KZZ-98 162.400 MHz
Valdez, AK WXJ-63 162.55 MHz
Cordova, AK WXJ-79 162.40 MHz
Whittier, AK KXI-29 162.40 MHz
AIDS TO NAVIGATION
Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.
COLREGS, 80.1705 (see note A)
International Regulations for Preventing Collisions at Sea, 1972.
The entire area of this chart falls seaward of the COLREGS Demarcation Line.
UNAKWIK INLET
Wells Bay
Foul
Fish Trap
PA (Rep 2011)
05'
04'
03'
02'
01'
61°
59'
58'
57'
Joins page 15



12

Note: Chart grid lines are aligned with true north.

Printed at reduced scale.

SCALE 1:50,000

Nautical Miles

1 0 1 2 3 4

Yards

1000 0 1000 2000 3000 4000 5000 6000

See Note on page 5.


Joins page 9
Eaglek Glacier
Cascade Bay
Schoppe Bay
Mueller Cove
Eaglek Bay
Derickson Bay
Kiniklik
Pt Pellew
Kiniklik I
Papoose Cove
Squaw Bay
Joins page 14
Joins page 17
L INFORMATION
Height referred to datum of soundings (MLLW)
an Higher gh Water | Mean High Water | Mean Low Water | Extreme Low Water
feet | feet | feet | feet
11.5 | 13.5 | 1.3 | -4.0
15.7 | 14.9 | 1.7 | -4.0
12.1 | 11.2 | 1.6 | -4.0
12.1 | 11.2 | 1.5 | -4.0
UTION
ELINES AND CABLES
pipelines and submarine
pipeline and cable areas
Cable Area



Note: Chart grid lines are aligned with true north.

Printed at reduced scale. ~~SCALE 1:50,000~~

Nautical Miles: 1 0 1 2 3 4

Yards: 1000 0 1000 2000 3000 4000 5000 6000

See Note on page 5.


Joins page 11
Cedar Bay
Granite Bay
Unakwik Pt
Fairmount I
Little Fairmount I
Outpost I
Olsen I
Cove
Platform
Foul
Co
Wd
57'
56'
55'
54'
53'
52'
51'
50'
49'
JOINS CHART 16713
Joins page 19



1st Ed., Sept. 25/99 ■

16712

CAUTION

This chart has been corrected from the Notice to Mariners published weekly by the National Imagery and Mapping Agency and the Local Notice to Mariners issued periodically by each U.S. Coast Guard district to the date shown in the lower left hand corner.

SOUNDINGS IN FA

(FATHOMS AND FEET TO 11 FATH

16

Note: Chart grid lines are aligned with true north.

Printed at reduced scale. ~~SCALE 1:50,000~~ See Note on page 5.

Nautical Miles: 1 0 1 2 3 4

Yards: 1000 0 1000 2000 3000 4000 5000 6000



THOMS
(HOMS)

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

FATHOMS	1	2	3	4	5	6	7	8	9	10	11	12	
FEET	6	12	18	24	30	36	42	48	54	60	66	72	
METERS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23



HOMS

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

FATHOMS	1 2 3 4 5 6 7 8 9 10 11 12 13 14
FEET	6 12 18 24 30 36 42 48 54 60 66 72 78 84
METERS	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26

Note: Chart grid lines are aligned with true north.

Printed at reduced scale.

~~SCALE 1:50,000~~
Nautical Miles
1 0 1 2 3 4
Yards
1000 0 1000 2000 3000 4000 5000 6000

See Note on page 5.



UNAKWIK INLET TO ESTHER PASSAGE AND COLLEGE FIORD

SOUNDINGS IN FATHOMS - SCALE 1:50,000

16712

ED NO. 1

NSN 7642014563660

NIMA STOCK NO. 16ACO16712

EMERGENCY INFORMATION

VHF Marine Radio channels for use on the waterways:

Channel 6 – Inter-ship safety communications.
Channel 9 – Communications between boats and ship-to-coast.
Channel 13 – Navigation purposes at bridges, locks, and harbors.
Channel 16 – Emergency, distress and safety calls to Coast Guard and others, and to initiate calls to other vessels. Contact the other vessel, agree to another channel, and then switch.
Channel 22A – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here.
Channels 68, 69, 71, 72 and 78A – Recreational boat channels.

Getting and Giving Help — Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.

Distress Call Procedures

- Make sure radio is on.
- Select Channel 16.
- Press/Hold the transmit button.
- Clearly say: "MAYDAY, MAYDAY, MAYDAY."
- Also give: Vessel Name and/or Description; Position and/or Location; Nature of Emergency; Number of People on Board.
- Release transmit button.
- Wait for 10 seconds — If no response Repeat MAYDAY call.

HAVE ALL PERSONS PUT ON LIFE JACKETS!

All Hazards NOAA Weather Radio NOAA's National Weather Service

NOAA Weather Radio All Hazards (NWR) is a nationwide network of radio stations broadcasting continuous weather information directly from the nearest National Weather Service office. NWR broadcasts official Weather Service warnings, watches, forecasts and other hazard information 24 hours a day, 7 days a week.
http://www.nws.noaa.gov/nwr/

Quick References

Nautical chart related products and information	—	**http://www.nauticalcharts.noaa.gov**
Online chart viewer	—	**http://www.nauticalcharts.noaa.gov/mcd/NOAAChartViewer.html**
Report a chart discrepancy	—	**http://ocsdata.ncd.noaa.gov/idrs/discrepancy.aspx**
Chart and chart related inquiries and comments	—	**http://ocsdata.ncd.noaa.gov/idrs/inquiry.aspx?frompage=ContactUs**
Chart updates (LNM and NM corrections)	—	**http://www.nauticalcharts.noaa.gov/mcd/updates/LNM_NM.html**
Coast Pilot online	—	**http://www.nauticalcharts.noaa.gov/nsd/cpdownload.htm**
Tides and Currents	—	**http://tidesandcurrents.noaa.gov**
Marine Forecasts	—	**http://www.nws.noaa.gov/om/marine/home.htm**
National Data Buoy Center	—	**http://www.ndbc.noaa.gov/**
NowCoast web portal for coastal conditions	—	**http://www.nowcoast.noaa.gov/**
National Weather Service	—	**http://www.weather.gov/**
National Hurrican Center	—	**http://www.nhc.noaa.gov/**
Pacific Tsunami Warning Center	—	**http://ptwc.weather.gov/**
Contact Us	—	**http://www.nauticalcharts.noaa.gov/staff/contact.htm**

twitter —— For the latest news from Coast Survey, follow **@nauticalcharts**



This Booklet chart has been designed for duplex printing (printed on front and back of one sheet). If a duplex option is not available on your printer, you may print each sheet and arrange them back-to-back to allow for the proper layout when viewing.

NOAA's Office of Coast Survey The Nation's Chartmaker